

## SUREGUARD STERLING SILVER 35

Silver Reflective Solar Control Film



Heat and Glare Control Film providing maximum performance levels where severe discomfort is experienced.

### BENEFITS

Reduces Glare

Reduces Heat Increase

Reduces Air Conditioning Costs

Improves Working Environments

Provides One Way Vision Performance

Limits Fading of Furnishings

### PERFORMANCE DATA

Total Solar Energy Rejection	%	61
Solar Heat Gain Reduction	%	54
Visible Glare Reduction	%	62
Shading Co-efficient	%	0.45
Visible Light Transmission	%	34
Visible Light Reflection (External)	%	38
Visible Light Reflection (Internal)	%	36
Ultra Violet Transmission - Less than	%	<99
Total Solar Energy Absorption	%	40
Total Solar Reflection	%	35
Total Solar Transmission	%	25
U' Factor	%	5.79
Film Construction & Thickness		50 micron
Film Colour		Silver

### FILM / GLASS COMPATIBILITY GUIDELINES

Glass Type	Clear S/G	Clear D/G	Tinted S/G	Tinted D/G
Float /Annealed	Yes	Yes	No	No
Toughened	Yes	Yes	Yes	Yes
Laminated	Yes	No	No	No
Georgian Wired	No	No	No	No

Sureguard Window Films®  
18a Beech Street  
Barnsley  
South Yorkshire  
S70 4HT

Tel: 0844 800 9066

enquiries@sureguard.co.uk

www.sureguard.co.uk

All values are as applied to 6mm clear glass and as determined by the manufacturers and independent testing laboratories.