## **SUREGUARD STERLING SILVER 50**

Silver Reflective Solar Control Film



Heat and Glare Control Film providing maximum performance levels where severe discomfort is experienced.

## **BENEFITS**

Reduces Glare

Reduces Heat Increase

Reduces Air Conditioning Costs

Improves Working Environments

Provides One Way Vision Performance

Limits Fading of Furnishings

## PERFORMANCE DATA

Total Solar Energy Rejection	%	48		
Solar Heat Gain Reduction	%	39		
Visible Glare Reduction	%	41		
Shading Co-efficient	%	.60		
Visible Light Transmission	%	53		
Visible Light Reflection (External)	%	23		
Visible Light Reflection (Internal)	%	22		
Ultra Violet Transmission - Less than	%	<99		
Total Solar Energy Absorption	%	39		
Total Solar Reflection	%	23		
Total Solar Transmission	%	38		
U' Factor		5.8		
Film Construction & Thickness		50 micron		
Film Colour		Silver		

FILM / GLASS COMPATIBILITY GUIDELINES						
Glass Type	Clear S/G	Clear D/G	Tinted S/G	Tinted D/G		
Float /Annealed	Yes	Yes	No	No		
Toughened	Yes	Yes	Yes	Yes		
Laminated	Yes	No	No	No		
Georgian Wired	No	No	No	No		

Sureguard Window Films® 18a Beech Street Barnsley South Yorkshire S70 4HT

Tel: 0844 800 9066

enquiries@sureguard.co.uk

www.sureguard.co.uk

All values are as applied to 6mm clear glass and as determined by the manufacturers and independent testing laboratories.