

SUREGUARD SAFETY FILM EXTERNAL

100 Micron Safety Film



A single ply safety film designed to upgrade existing glass to the requirements of BS6206 and Regulation 14 of the Workplace (Health, Safety & Welfare) Regulations 1992.

BENEFITS

- Improves Glass Safety
- Protects Against Injury
- Reduces Clear Up Time
- Protects Against Flying Glass
- Improves Building Security
- Limits Fading of Furnishings

PERFORMANCE DATA

Total Solar Energy Rejection	%	18
Solar Heat Gain Reduction	%	4
Visible Glare Reduction	%	1
Shading Co-efficient	%	.95
Visible Light Transmission	%	89
Visible Light Reflection	%	10
Ultra Violet Transmission - Less than	%	<99
Total Solar Absorption	%	14
Total Solar Reflection	%	8
Total Solar Transmission	%	78
U' Factor	%	1.04
Film Construction & Thickness		100 Micron
Film Colour		Clear

CERTIFICATIONS & PERFORMANCE

BS6206 Classification	BS6206 Class B
BSEN Classification	BS EN12600 Class 2B
ANSI Classification	ANSI Z97.1 Class B
Peel Strength after one week	>2500
Tensile Strength at Break (MD/TD)	200
Elongation at Break MD	>100%

FILM / GLASS COMPATIBILITY GUIDELINES

Glass Type	Clear S/G	Clear D/G	Tinted S/G	Tinted D/G
Float /Annealed	Yes	Yes	Yes	Yes
Toughened	Yes	Yes	Yes	Yes
Laminated	Yes	Yes	Yes	Yes
Georgian Wired	Yes	Yes	Yes	Yes

Sureguard Window Films®
18a Beech Street
Barnsley
South Yorkshire
S70 4HT

Tel: 0844 800 9066

enquiries@sureguard.co.uk

www.sureguard.co.uk

All values are as applied to 6mm clear glass and as determined by the manufacturers and independent testing laboratories.