SUREGUARD STERLING SILVER 50

Silver Reflective Solar Control Film



Heat and Glare Control Film providing maximum performance levels where severe discomfort is experienced.

BENEFITS

Reduces Glare

Reduces Heat Increase

Reduces Air Conditioning Costs

Improves Working Environments

Limits Fading of Furnishings

PERFORMANCE DATA

Total Solar Energy Rejection	%	48		
Solar Heat Gain Reduction	%	39		
Visible Glare Reduction	%	41		
Shading Co-efficient	%	.60		
Visible Light Transmission	%	53		
Visible Light Reflection (External)	%	23		
Visible Light Reflection (Internal)	%	22		
Ultra Violet Transmission - Less than	%	<99		
Total Solar Energy Absorption	%	39		
Total Solar Reflection	%	23		
Total Solar Transmission	%	38		
U' Factor		5.8		
Film Construction & Thickness		50 micron		
Film Colour		Silver		

FILM / GLASS COMPATIBILITY GUIDELINES						
Glass Type	Clear S/G	Clear D/G	Tinted S/G	Tinted D/G		
Float /Annealed	Yes	Yes	No	No		
Toughened	Yes	Yes	Yes	Yes		
Laminated	Yes	No	No	No		
Georgian Wired	No	No	No	No		

Sureguard Window Films®
18a Beech Street
Barnsley
South Yorkshire
S70 4HT

Tel: 0844 800 9066

enquiries@sureguard.co.uk

www.sureguard.co.uk

All values are as applied to 6mm clear glass and as determined by the manufacturers and independent testing laboratories.